



TECHNICAL DATA SHEET

Product Name

Speedy Fix

HUZHOU GUONENG NEW MATERIAL CO.LTD

Company address: No.1518, Mengxi Road, Huzhou Zhejiang China.

Tel: 0086-572-2109399

Fax: 0086-572-2352225

Email: Sales@visbella.com

Website: www.visbella.com

PRODUCT DESCRIPTION

Speedy Fix is the latest development in adhesive technology.It will bond nearly all types of materials and can be used to fill cracks,holes and gaps with the reinforcing powders provided.

PHYSICAL PROPERTIES

Appearance	Black/Clear/Black/Red/Yellow/Blue/Green/White
Density(g/cm ³)	1.4~2.4
Hardness(mpa)	80~220
Melting point(°C)	600~1200



PRODUCT BENEFITS

- 1.Rapid solidification
- 2.Strong cohesive force
- 3.Widely usage.
- 4.Easy to us

DIRECTIONS FOR USE

Repairs almost anything from toys,PVC's,and tools ,automotive&many more.

The Powder to repair Bumper, Grilles, Radiators, Motorcycle Fairings, Electrical Switches, Door Handles, Distributor caps and so much more.

- 1.Ensure that the paint is removed and that the surface is clean, dry and roughened.
- 2.Apply powder to area being repaired and then drip Speedy Fix onto the powder, making sure that the bottle and/or applicator doesn't touch the powder.
- 3.To replace fill missing parts, place tape underneath the gap, fill with powder and apply Speedy Fix super glue. Remove the tape after Speedy Fix hardens.
- 4.Don't cut the bottle open, pierce with the pin supplied and seal after use.

NOTE

Experience has shown that bonded tissues are best treated by passive, non-surgical first aid. If rapid curing has caused thermal burns they should be treated symptomatically after adhesive is removed.

STORAGE

Keep in a cool, well ventilated area away from heat, sparks and open flame. Keep container tightly closed until ready for use.